

Serial No.10/755,135

Amendments to the Specification:

Kindly amend the paragraph beginning at page 5,
line 15, as follows:

b) two finger guards 12 and 13 upstanding
from a side 11a of the plate, and having intermediate
spacing 14 therebetween to receive a user's middle finger 15
to extend adjacent to the plate,

Kindly amend the paragraph beginning at page 5,
line 19, as follows:

c) ~~each finger guard having a~~ the finger guards
have finger retention ~~portion~~ portions 12a and 13a
overhanging the plate to provide for adjustable spaces 16
and 17 to receive the user's first and third fingers,
between the overhang portions and the plate. As shown in
the drawings, the overhanging portions project with
curvature in opposite direction, and away from each other
and with convexity toward said intermediate spacing whereby
said intermediate spacing between the guards has venturi
shape in a direction away from the plate.

Serial No.10/755,135

Kindly amend the paragraph beginning at page 5, line 24, and continuing to page 5, line 1, as follows:

As shown, the finger retention portions 12a and 13a, are arcuate, and have concave sides facing the plate, each guard having a terminal spaced from the plate, whereby the guard has cantilever support by the plate. See bulbous terminals 12b and 13b. See also the plate concave side 11a facing toward the finger guards. The guards have spaced, arcuate projecting portions defining said middle finger space 14 therebetween.